

DISCHARGE MEASUREMENTS AT ARAYAT GAUGING STATION, PAMPANGA RIVER (SAN AGUSTIN, ARAYAT, PAMPANGA)



A Technical Report

Presented to

**Mr. Hilton T. Hernando
Mr. Socrates F. Paat Jr.
Mr. Roy A. Badilla**

**In Partial Fulfillment of the Requirements for
Stream Gauging II
Hydrologists Training Course (HTC)
Philippine Atmospheric, Geophysical and
Astronomical Services Administration (PAGASA)
Department of Science and Technology (DOST)**

GALANIDA, VER LANCER D.

18 November 2013



ACKNOWLEDGEMENTS

It is with great pleasure that I express my gratitude to the individuals who gave me assistance, ideas and insights in our fieldwork activities, and the compilation and preparation process, and enabled this enormous task to be accomplished.

I express my deep appreciation and sincere thanks to my instructors in Stream Gauging, mentors and guides during our fieldwork activities: ***Mr. Hilton T. Hernando, Mr. Socrates F. Paat Jr., Mr. Roy A. Badilla,*** and the whole PRFFWC staffs; to my group mates: ***Engr. Ramjun Sajulga, Ms. Vhan Therese Singson, Engr. Victor Flores, Ms. Shelly Jo Ignacio, Ms. Mary May Victoria Calimoso, Engr. Junie Ruiz,*** and ***Engr. Alexander Namoco;*** to my great classmates/aspirant hydrologists: ***Engr. Romeo Aguirre, Engr. Manny John Agbay, Engr. Benison Jay Estareja, Ms. Iveil Mae Bajuyo, Engr. Heart Cipriano, Engr. Bema Cominador, Engr. Lorenzo Puerto, Engr. Rex Abdon Jr., Engr. Sheila Joy Go-oc, Engr. Araya Mahilum, Engr. Raul Montilla, Ms. Shaira Ann Nonot, Ms. Allen Buendia, Engr. Vivian Gay Aggasid, , Engr. Darwin Dikitanan, Engr. Loreto Lavadia, Engr. Reniel Mago, Engr. Ronaldo Naragdao, Engr. Francis Reonal, Engr. Daniel Caber, Engr. Angelo Fernandez, Mr. Leo Ortega, Mr. Ruben Wamuni and Mr. Paula Tawakece;*** to the rest of our instructors in Hydrologists Training Course (HTC), the staffs of Training and Public Information Section, our second mother, ***Ms. Encarnation A. Borjal,*** and to my beloved family way back home.

I thank you!

TABLE OF CONTENTS

	Page
1.0 INTRODUCTION.....	1
2.0 OBJECTIVES.....	2
3.0 SITE LOCATION.....	2
4.0 SITE DESCRIPTION.....	3
5.0 PREPARATION.....	4
6.0 METHODOLOGY.....	4
7.0 DISCUSSIONS AND COMPUTATIONS FOR EACH METHOD.....	4
7.1.0 Slope – Area Method.....	5
7.2.0 Using Acoustic Doppler Current Profiler.....	16
7.3.0 Using Currentmeter.....	20
7.4.0 Float Method.....	26
8.0 CONCLUSION ON THE VARIOUS METHODS OF DISCHARGE MEASUREMENTS.....	32
9.0 DEVELOPMENT OF A RATING CURVE, EQUATION AND TABLE.....	33
10.0 FIELD VISITS.....	41
10.1 La Mesa Dam.....	41
10.2 Pantabangan Dam.....	42
10.3 Cong Dadong Dam.....	43
10.4 MDRRMC Calumpit, Bulac.....	43
10.5 Angat Dam.....	44
10.6 Bacoor Church.....	45
11.0 FIELDTRIP/FIELDWORK EVALUATION.....	46

1.0 INTRODUCTION



Figure 1. The 4 methods being used during the fieldwork.

It is always a given that when stream flow occurs in excess, it can create a hazard like flood that causes extensive damages and hardships. However, the measurement of stream flow is amenable to fairly accurate assessment.

On October 11, 2013, Typhoon Santi, also called “Sari”, caused flooding in some portion of Pampanga as it hit toward Luzon under storm warning signal number 2 (number 3 for some other areas). The heavy rains brought by the typhoon had caused the Pampanga River, particularly at Arayat Station, to overflow and generate floods over the surrounding area. It was then a good timing that the Hydrologists Training Course (HTC) of Philippine Atmospheric, Geophysical and Astronomical Services Administration (PAGASA) were scheduled to have a fieldwork at Pampanga few days after the flooding. This led the HTC and the Pampanga River Flood Forecasting and Warning Center (PRFFWC) to grab the good opportunity, as conducting a survey and measuring the discharge of the river is very suitable to be performed after a flood event. Fully assisted by the staffs of PRFFWC, discharge measurement, the basic work on field of a hydrologist, was executed and performed by the trainees.

During the fieldwork, the methods that were being used for determining the quality of water flowing in channels are of four (4) kinds: the discharge measurement using Currentmeter, the Slope-Area Method, the Float Method, and the discharge measurement using Acoustic Doppler Current Profiler (ADCP).

2.0 OBJECTIVES

The main objective of the report is to measure the discharge of Pampanga River at Arayat Guaging Station at relatively low flow using the four (4) different methods: the discharge measurement using Currentmeter, using Acoustic Doppler Current Profiler (ADCP), the Slope-Area Method, and the Float Method. The specific objectives are as follows:

1. To conduct discharge measurements using the four (4) different methods, and give analysis and suggestions for each of these methods.
2. To give brief review and personal views on the hydrology-related field sites being visited for the whole duration of the fieldwork/ fieldtrip.
3. To evaluate the whole fieldwork activities in general.
4. To be able to produce a well-presented technical report for the purpose of preparation and training for future concern as an aspiring hydrologist.

3.0 SITE LOCATION



The discharge measurements were performed at Arayat Station, Pampanga River, located at Highway bridge along Olongapo - Gapan Road, Barrio San Agustin, Arayat, Pampanga.

Figure 2. The location of Arayat Station, Pampanga River (Google Earth image).

4.0 SITE DESCRIPTION



Figure 2. Physical features of the site.

Pampanga River has about 260 kilometers length. Arayat Station, one of its stations maintained and monitored by PAGASA, lies on the middle of the river. It has a gaging station located at the right bank of the river, downstream of San Agustin Bridge along the GSO highway at Brgy Camba, Arayat, Pampanga. Based on the 2009 survey by PRFFWC, this station has an estimated elevation of 9 meters and Staff Gauge (S.G.) “0” gage elevation of 0.077 meter based on the Mean Sea Level (MSL) with an old telepole benchmark (BM).

The site is not unduly exposed to wind, and is easily accessible, with available uniform reach. The river reach downstream is not perfectly fairly straight but considerable for discharge measurement, having stable bed and banks. Since it was just few days after the occurrence of flood, the flow in the reach is not so free from significant disturbances, draw-down or back-water, as traces of debris and mud on structures and trees were captured. The orientation of the reach is normal, such that the direction of the flow is as close as normal to that of the prevailing wind. Grasses and reeds that run along the river’s right bank near the water edge are observable, but beyond that, a number of trees dotting the agricultural field exist and terrain was relatively flat. The soil at both banks, as also observed on its river bed, was a mixture of gravel, silt, sand, clay, and pebbles.

5.0 PREPARATION

Prior to leaving for the field site, preparations were made anticipating the weather, safety, tools, equipment, and other supply needs. All tools and equipment being used for discharge measurements were brought by the PRFFWC staffs. The trainees were equipped with proper field clothing and accurate instructions about the works on the field. The staffs of PRFFWC were assisting the aspirant hydrologists in performing discharge measurement in all four (4) methods. The fieldwork lasted for four days only (October 17, 18, 21 and 22), but the entire fieldtrip and fieldwork activities were good for ten days (October 16 to 24).

6.0 METHODOLOGY

Four groups from the trainees were created and four different methods of discharge measurement were assigned to be performed by each group. On the first day of the fieldwork, as for our group with eight members, we were tasked to obtain data for slope-area method of discharge measurement, ADCP measurements on the second day, current meter measurements on the third day and measurement by float on the fourth day. The discussions, measurements, computations, personal views, and conclusions will be presented in this manner.

7.0 DISCUSSIONS AND COMPUTATIONS

Stream gaging is a technique used to measure the discharge, or the volume of water moving through a channel per unit time, of a stream. Discharge is measured by integrating the area and velocity of each point across the stream; that is, the stream is divided into sections based on where velocity and stage height measurements were taken in the cross-section of the stream.

The team performing the measurement has a big role on the field. Reliable stream gage data is dependent on the care and consistency field personnel apply to their field stream gaging techniques. Following proper instructions and applying what we have learned from our previous lectures and discussions in Stream Gauging I and II, and Introduction to Surveying, our group did our best in the execution of the discharge measurements. The data we have gathered were computed and we came up with different discharge measurement for different methods performed on different days.

7.1.0 SLOPE – AREA METHOD

Slope-Area method is good for estimating flood peaks which cannot otherwise be measured. It is a technique for estimating the peak discharge of a flood after the water has receded. This type of discharge estimate is called an “indirect measurement” because it relies on evidence left behind by the flood, such as high-water marks (HWMs) on trees or buildings.

7.1.1 TECHNIQUES AND CROSS SECTION SURVEY

On the first day on field for slope-area method, the bench mark was identified first and foremost to determine the known elevation of the site. A benchmark located at the left bank at about 100 meters northwest from San Agustin Bridge was used for the survey. It has an elevation of 9.114 AMSL, within the vicinity of the old gaging station and was located at the concrete foundation of an antenna post that was no longer there. Benchmark was run across the right bank downstream of the bridge, where a reach starting at 53 meters from the bridge and with a total length of 300 meters was surveyed for the slope-area measurements. The highest flood marks were sited at both banks manually. These high water marks (HWM) were used as reference points for the cross sections. Using the total station and the prism, the elevation of the farthest HWM on both banks were identified. Some points in between the HWMs were also identified to complete the cross section.

Meanwhile, some of our group members were collecting other data to come up with our cross sections. The reach surveyed was divided into three cross-sections 150 meters apart. The 53 meter distance from the bridge was determined by tape and the subsequent intervals of 150 meters up to 300 meters were determined by a range-finder. An echo sounder was submerged in the river at different parts of the river just along the path of the HWMs on both banks. This process was repeated for the other two cross sections. The gauge height at the start and end of the method was recorded.




Figure 3. Illustration on how slope-area method was done.

The following tables show the summary of the survey that was done for each cross section, going from left bank to right bank:

FIRST CROSS-SECTION				
POINT	DISTANCE			ELEVATION
	ACTUAL	CORRECTED	ACCUMULATED CORRECTED	
P1	0	0	0	8.6
P2	20	20.00	20	8.272
P3	2.2	2.20	22.2	7.072
P4	2.66	2.66	24.86	4.782
P5	5	5.00	29.86	-2.618
P6	9	9.00	38.86	-0.618
P7	9	9.00	47.86	-2.418
P8	7	7.00	54.86	-6.118
P9	9	9.00	63.86	-6.818
P10	5	5.00	68.86	-5.718
P11	15	15.00	83.86	-4.418
P12	9	9.00	92.86	-1.218


P13	4	4.00	96.86	-1.618
P14	14	14.00	110.86	0.682
P15	7	7.00	117.86	0.482
P16	16	16.00	133.86	1.382
P17	3	3.00	136.86	1.582
P18	20	20.00	156.86	3.882
P19	22	22.00	178.86	4.782
P20	5	5.00	183.86	6.575
P21	36	36.00	219.86	7.349
P22	20	20.00	239.86	7.424
P23	19	19.00	258.86	7.857
P24	25	25.00	283.86	8.514
P25	11	11.00	294.86	8.478
P26	15	15.00	309.86	8.431
P27	32	32.00	341.86	6.879
P28	7.5	7.50	349.36	6.928
P29	7.5	7.50	356.86	7.094
P30	2.5	2.50	359.36	7.279
P31	10	10.00	369.36	7.667
P32	10	10.00	379.36	8.6



SECOND CROSS-SECTION				
POINT	DISTANCE			ELEVATION
	ACTUAL	CORRECTED	ACCUMULATED CORRECTED	
P1	0	0	0.0	8.552
P2	7.00	7.00	7.0	4.895
P3	1.41	1.41	8.4	4.185
P4	9.67	9.67	18.1	-1.805
P5	2.64	2.64	20.7	-2.205
P6	21.10	21.10	41.8	-2.705
P7	9.67	9.67	51.5	-1.305
P8	18.46	18.46	70.0	-1.305
P9	18.46	18.46	88.4	-0.405
P10	7.03	7.03	95.5	0.195
P11	13.19	13.19	108.6	0.595
P12	9.67	9.67	118.3	1.395
P13	3.52	3.52	121.8	1.395
P14	16.71	16.71	138.5	2.095
P15	16.48	16.48	155.0	3.695

P16	1.99	1.99	157.0	4.895
P17	6.00	3.00	160.0	7.103
P18	6.10	1.50	161.5	7.117
P19	36.00	36.00	197.5	7.106
P20	25.00	20.50	218.0	8.5


THIRD CROSS-SECTION				
POINT	HORIZONTAL DISTANCE			ELEVATION
	ACTUAL	CORRECTED	ACCUMULATED CORRECTED	
P1	0	0	0	7.797
P2	11	6.00	6	5.244
P3	3.34	3.34	9.34	3.844
P4	0.957	0.96	10.297	-0.156
P5	0.955	0.96	11.252	-1.556
P6	34.378	34.38	45.63	-1.356
P7	14.32	14.32	59.95	-0.456
P8	3.82	3.82	63.77	-0.756
P9	16.24	16.24	80.01	-0.256
P10	19.098	19.10	99.108	0.744
P11	12.412	12.41	111.52	0.644
P12	7.642	7.64	119.162	1.144
P13	8.595	8.60	127.757	1.144
P14	13.369	13.37	141.126	1.444
P15	5.73	5.73	146.856	1.544
P16	16.712	16.71	163.568	4.824
P17	1.432	1.43	165	5.244
P18	1.5	1.50	166.5	6.166
P19	3	3.00	169.5	6.958
P20	53.5	53.00	222.5	7.259
P21	30.5	27.00	249.5	7.584
P22	24.5	24.00	273.5	7.483
P23	1	1.00	274.5	7.7

The following graphs are the illustrations for each cross section, shown from left bank to right bank with values for elevation based on the Mean Sea Level:






The illustrations below show the same cross sections plotted out in AutoCAD¹:



FIRST CROSS SECTION



SECOND CROSS SECTION



THIRD CROSS SECTION

7.1.2 ISSUES AND CONCERNS

The following are the imitations and difficulties that have arose in the slope-area method, as encountered by our group during the survey.

1. Identification of flood marks – In most cases during the survey, it is either difficult to assess the horizontal extent of the flood mark in the cross-section, or it may simply be inaccessible and hard to identify. In the first cross-section, we were able to identify the flood mark on the right bank but we were forced to estimate the extent of the flood because of barbed wire fences and accessibility issues. On the left bank of the same cross section, the flood mark was hard to identify so we had to ask the locals who were with us on the boat about how high the water was at that time of flooding and we also had to estimate the extent because the area was too muddy to walk through.
2. Tedious nature of the survey work – The whole activity was time consuming and tiring. The group had to survey the ground along 300 meters of the river downstream and on its


¹ The cross section and top view layout were also drawn in cross section sheets .

- banks, stepping on mud, crawling beneath barbed wires (whenever possible and allowed) and having to ask permission from residents to access their property for the survey work.
3. Stability of the boat used during the river survey – It was hard to maintain a straight line of depth measurement across the river because of the flow. There was no tagline used at the time because the tagline available wasn't enough to reach the other bank. We were forced to assume in our calculations that we traversed along a straight line.
 4. Equipment issues - For a moment during the survey, the total station suddenly went off. There was a problem with the equipment's power supply but it was fortunate that the group, together with our mentor at the time, was able to find a remedy. The range finder's readings were also inaccurate and the device cannot read the distance toward the opposite bank.
 5. Terrain – The ground was still muddy on the first day of measurements. The group had a difficulty finding a stable footing on which to measure the elevation of the ground, especially along the banks. This resulted in criss-cross measurement along the cross-section which is in contrast to an ideal straight-line measurement of elevation along a cross-section.
 6. General accessibility issues – The group had a hard time measuring elevation at some points in the area simply because we could not access it. Some challenges encountered were knee-deep mud, barbed wire fences and thick bushes.

7.1.3 COMPUTATIONS OF DISCHARGE

Data gathered for the cross sections were entered in the Slope-Area excel suite provided by our instructor, Mr Hilton T. Hernando. The cross section data were entered from left bank to right bank. The results were as follows:

DISCHARGE MEASUREMENTS AT ARAYAT ATATION | 2013

				Republic of the Philippines Department of Science and Technology PHILIPPINE ATMOSPHERIC, GEOPHYSICAL AND ASTRONOMICAL SERVICES ADMINISTRATION (PAGASA) Pampanga River Flood Forecasting and Warning Center (PRFFC) Agham Road, Diliman, Quezon City																																																															
FFB, PAGASA		Slope-Area Summary Sheet (3-Section)																																																																	
Station:		Arayat				River:		Pampanga River																																																											
Flood Date:		13-Oct-13				Drainage Area:		6,487																																																											
Gauge Height:		8.78				Meas. #:																																																													

X - Section Properties:																																																																			
<table border="1"> <thead> <tr> <th rowspan="2">X- Sect.</th> <th rowspan="2">Width</th> <th rowspan="2">Area</th> <th colspan="2">Highwater Marks</th> <th rowspan="2">Average Water Sfc.</th> <th rowspan="2">d_m (mean depth)</th> <th rowspan="2">n</th> <th rowspan="2">r</th> <th rowspan="2">K</th> <th rowspan="2">K³/A²</th> <th rowspan="2">α</th> <th rowspan="2">F</th> <th rowspan="2">State of Flow</th> </tr> <tr> <th>Left Bank</th> <th>Right Bank</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>379.36</td> <td>1623.42</td> <td>8.272</td> <td>8.6</td> <td>8.436</td> <td>4.279</td> <td>0.04</td> <td>4.19</td> <td>106006.9</td> <td>4.5E+08</td> <td>1</td> <td>0.379</td> <td>tranquil</td> </tr> <tr> <td>2</td> <td>218.00</td> <td>1355.39</td> <td>8.552</td> <td>8.5</td> <td>8.526</td> <td>6.217</td> <td>0.04</td> <td>6.10</td> <td>113808.7</td> <td>8E+08</td> <td>1</td> <td>0.377</td> <td>tranquil</td> </tr> <tr> <td>3</td> <td>274.50</td> <td>1221.98</td> <td>7.797</td> <td>7.7</td> <td>7.7485</td> <td>4.452</td> <td>0.04</td> <td>4.36</td> <td>81973.56</td> <td>3.7E+08</td> <td>1</td> <td>0.494</td> <td>tranquil</td> </tr> </tbody> </table>										X- Sect.	Width	Area	Highwater Marks		Average Water Sfc.	d _m (mean depth)	n	r	K	K ³ /A ²	α	F	State of Flow	Left Bank	Right Bank	1	379.36	1623.42	8.272	8.6	8.436	4.279	0.04	4.19	106006.9	4.5E+08	1	0.379	tranquil	2	218.00	1355.39	8.552	8.5	8.526	6.217	0.04	6.10	113808.7	8E+08	1	0.377	tranquil	3	274.50	1221.98	7.797	7.7	7.7485	4.452	0.04	4.36	81973.56	3.7E+08	1	0.494	tranquil
X- Sect.	Width	Area	Highwater Marks		Average Water Sfc.	d _m (mean depth)	n	r	K				K ³ /A ²	α										F	State of Flow																																										
			Left Bank	Right Bank																																																															
1	379.36	1623.42	8.272	8.6	8.436	4.279	0.04	4.19	106006.9	4.5E+08	1	0.379	tranquil																																																						
2	218.00	1355.39	8.552	8.5	8.526	6.217	0.04	6.10	113808.7	8E+08	1	0.377	tranquil																																																						
3	274.50	1221.98	7.797	7.7	7.7485	4.452	0.04	4.36	81973.56	3.7E+08	1	0.494	tranquil																																																						
note: Assume no sub-divided sections, hence α is always 1!!																																																																			
Reach Properties:																																																																			
Reach	Length	Δh Fall	k	reach condition	K _U /K _D	K _U /K _D Condition	Ave. A	Q by formula	Ave V																																																										
1-2	150	-0.09	0	contracting	0.931448	good	1489.403	x	x																																																										
2-3	150	0.7775	0	contracting	1.388359	good	1288.681	5881.839	4.564																																																										
1-2-3	300	0.6875	0	contracting	1.293184	good	1400.260	3983.727	2.845																																																										
Discharge Computation:(comparison)																																																																			
Reach	Assumed Q	U/S	D/S	Δh _v	h _f	S=h _f /L	S ^{1/2}	K _w	Computed Q																																																										
1-2	x	0.307229	0.440754	-0.13353	-0.22353	-0.00149	x	109838.6	x																																																										
2-3	5881.839	0.440754	0.542249	-0.10149	0.676006	0.004507	0.067132	96588.32	6484.168																																																										
Rem:																																																																			
Discharge									Q ₁₋₂₋₃ = 3983.73 cumecs																																																										

DISCHARGE MEASUREMENTS AT ARAYAT ATATION | 2013

Slope-Area Cross-Section Computation

Station:	Arayat				Survey Date:	17-Oct-13	
River:	Pampanga				Gage Ht. =	5.31	meters
Cross-Section number ONE (1)							
Station	Distance	Elevation	Water Sfc. elev.	Depth	Mean Depth	Area	Wetted Perimeter
0		8.6	8.6	0			
20	20	8.272	8.6	0.328	0.164	3.28	20.00269
22.2	2.2	7.072	8.6	1.528	0.928	2.0416	2.505993
24.86	2.66	4.782	8.6	3.818	2.673	7.11018	3.509943
29.86	5	-2.618	8.6	11.218	7.518	37.59	8.930845
38.86	9	-0.618	8.6	9.218	10.218	91.962	9.219544
47.86	9	-2.418	8.6	11.018	10.118	91.062	9.178235
54.86	7	-6.118	8.6	14.718	12.868	90.076	7.917702
63.86	9	-6.818	8.6	15.418	15.068	135.612	9.027181
68.86	5	-5.718	8.6	14.318	14.868	74.34	5.11957
83.86	15	-4.418	8.6	13.018	13.668	205.02	15.05623
92.86	9	-1.218	8.6	9.818	11.418	102.762	9.551963
96.86	4	-1.618	8.6	10.218	10.018	40.072	4.01995
110.86	14	0.682	8.6	7.918	9.068	126.952	14.18767
117.86	7	0.482	8.6	8.118	8.018	56.126	7.002857
133.86	16	1.382	8.6	7.218	7.668	122.688	16.02529
136.86	3	1.582	8.6	7.018	7.118	21.354	3.006659
156.86	20	3.882	8.6	4.718	5.868	117.36	20.13182
178.86	22	4.782	8.6	3.818	4.268	93.896	22.0184
183.86	5	6.575	8.6	2.025	2.9215	14.6075	5.311765
219.86	36	7.349	8.6	1.251	1.638	58.968	36.00832
239.86	20	7.424	8.6	1.176	1.2135	24.27	20.00014
258.86	19	7.857	8.6	0.743	0.9595	18.2305	19.00493
283.86	25	8.514	8.6	0.086	0.4145	10.3625	25.00863
294.86	11	8.478	8.6	0.122	0.104	1.144	11.00006
309.86	15	8.431	8.6	0.169	0.1455	2.1825	15.00007
341.86	32	6.879	8.6	1.721	0.945	30.24	32.03761
349.36	7.5	6.928	8.6	1.672	1.6965	12.72375	7.50016
356.86	7.5	7.094	8.6	1.506	1.589	11.9175	7.501837
359.36	2.5	7.279	8.6	1.321	1.4135	3.53375	2.506836
369.36	10	7.667	8.6	0.933	1.127	11.27	10.00752
379.36	10	8.6	8.6	0	0.4665	4.665	10.04343
Total Width =		379.36	meters	Hydraulic Radius(r) =		4.19	meters
Total Area =		1623.42	meters ²	Mean Section Depth =		4.279362	meters
Wetted Perimeter(P) =		387.344	meters				


Slope-Area Cross-Section Computation

Station: Arayat				Survey Date: 17-Oct-13			
River: Pampanga		Gage ht. = 5.31		meters			
Cross-Section number TWO (2)							
Station	Distance	Elevation	Water Sfc. elev.	Depth	Mean Depth	Area	Wetted Perimeter
0.0		8.552	8.5	-0.052			
7.0	7	4.895	8.5	3.605	1.7765	12.4355	7.897699
8.4	1.4068	4.185	8.5	4.315	3.96	5.570928	1.575813
18.1	9.6718	-1.805	8.5	10.305	7.31	70.70086	11.37646
20.7	2.6374	-2.205	8.5	10.705	10.505	27.70589	2.66756
41.8	21.104	-2.705	8.5	11.205	10.955	231.1943	21.10992
51.5	9.670166	-1.305	8.5	9.805	10.505	101.5851	9.770983
70.0	18.4643	-1.305	8.5	9.805	9.805	181.0424	18.4643
88.4	18.4643	-0.405	8.5	8.905	9.355	172.7335	18.48622
95.5	7.034018	0.195	8.5	8.305	8.605	60.52773	7.059562
108.6	13.18878	0.595	8.5	7.905	8.105	106.8951	13.19485
118.3	9.671775	1.395	8.5	7.105	7.505	72.58667	9.704805
121.8	3.517009	1.395	8.5	7.105	7.105	24.98835	3.517009
138.5	16.70579	2.095	8.5	6.405	6.755	112.8476	16.72045
155.0	16.47719	3.695	8.5	4.805	5.605	92.35464	16.55469
157.0	1.98711	4.895	8.5	3.605	4.205	8.355798	2.321337
160.0	3	7.103	8.5	1.397	2.501	7.503	3.724952
161.5	1.5	7.117	8.5	1.383	1.39	2.085	1.500065
197.5	36	7.106	8.5	1.394	1.3885	49.986	36
218.0	20.49956	8.5	8.5	0	0.697	14.28819	20.5469
Total Width =		218.00	meters	Hydraulic Radius(r) =		6.10	meters
Total Area =		1355.39	meters ²	Mean Section Depth =		6.21737	meters
Wetted Perimeter(P) =		222.194	meters				


Slope-Area Cross-Section Computation

Station:	Arayat			Survey Date:	17-Oct-13		
River:	Pampanga			Gage ht. =	5.31	meters	
Cross-Section number THREE (3)							
Station	Distance	Elevation	Water Sfc. elev.	Depth	Mean Depth	Area	Wetted Perimeter
0.0		7.797	7.7	-0.097			
6.0	6	5.244	7.7	2.456	1.1795	7.077	6.520568
9.3	3.34	3.844	7.7	3.856	3.156	10.54104	3.621547
10.3	0.957	-0.156	7.7	7.856	5.856	5.604192	4.112888
11.3	0.955	-1.556	7.7	9.256	8.556	8.17098	1.694705
45.6	34.378	-1.356	7.7	9.056	9.156	314.764968	34.37858
60.0	14.32	-0.456	7.7	8.156	8.606	123.23792	14.34825
63.8	3.82	-0.756	7.7	8.456	8.306	31.72892	3.831762
80.0	16.24	-0.256	7.7	7.956	8.206	133.26544	16.2477
99.1	19.098	0.744	7.7	6.956	7.456	142.394688	19.12416
111.5	12.412	0.644	7.7	7.056	7.006	86.958472	12.4124
119.2	7.642	1.144	7.7	6.556	6.806	52.011452	7.65834
127.8	8.595	1.144	7.7	6.556	6.556	56.34882	8.595
141.1	13.369	1.444	7.7	6.256	6.406	85.641814	13.37237
146.9	5.73	1.544	7.7	6.156	6.206	35.56038	5.730873
163.6	16.712	4.824	7.7	2.876	4.516	75.471392	17.03084
165.0	1.432	5.244	7.7	2.456	2.666	3.817712	1.492322
166.5	1.5	6.166	7.7	1.534	1.995	2.9925	1.760706
169.5	3	6.958	7.7	0.742	1.138	3.414	3.102783
222.5	53	7.259	7.7	0.441	0.5915	31.3495	53.00085
249.5	27	7.584	7.7	0.116	0.2785	7.5195	27.00196
273.5	24	7.483	7.7	0.217	0.1665	3.996	24.00021
274.5	1	7.7	7.7	0	0.1085	0.1085	1.023274
Total Width =		274.50	meters	Hydraulic Radius(r) =		4.36	meters
Total Area =		1221.98	meters ²	Mean Section Depth =		4.451640036	meters
Wetted Perimeter(P) =		280.062	meters				


Station:	Arayat	Date:	17-Oct-13
River:	Pampanga	Gage Ht.	5.31 meters
Total Area =	1623.42	meters ²	



Total Area = 1355.39 meters²



Total Area = 1221.98 meters²



The roughness coefficient, n , that was used by the group was 0.04. This is the roughness coefficient of vegetation, chosen because at the time of the flood, the wetted perimeter included the trees, reeds and bushes surrounding both banks. The estimated discharge at the time of the flood, by slope area method, was 3983.73 cubic meters per second.

7.1.4 CONCLUSION

The discharge determined by slope area method is, at best, only an approximate. This is due to the following reasons:


1. The reach under survey was not exactly straight. It gradually bends to the right when looking downstream of the bridge.
2. The rangefinder readings were inaccurate. This was later found out when the width of the river as computed from the readings of the total station and the width of the river measured with a range finder and measuring tape (used by members on the boat as the rangefinder cannot read out the distance toward the opposite bank at the time) were different. It was also by the use of the rangefinder that we established the 150 meter distance between the three cross-sections, which introduces another error in our calculations since it was these readings that were used in the excel suite.
3. The path traversed on the river was not actually straight. The tagline available that was supposed to guide the boat was not long enough to reach the other bank at the time. In the calculations, the group *assumed* a straight path of depth measurements across the river, with the cross section perpendicular to the flow.
4. Due to terrain restrictions mentioned previously (section 3.1.2), the elevation readings were not made exactly along the cross section established by a line connecting the right and left bank (with the exception of the first cross section). As a correction, we have to project a line from the actual readings perpendicular to the line of the cross section, marking the intersection and measuring the distance between intersections on a cross section sheet. This was how our corrected horizontal distances were established, based on the assumption that elevation is the same along a straight line perpendicular to the cross-section. This, of course, does not reflect what is exactly on field and affects the representativeness of the discharge measurement to some degree.

5. The horizontal extent of the flood mark on the right and left banks of the first cross section was only estimated due to accessibility issues. The flood mark on the left bank of the same cross section, on the other hand, was not identified on site because the area was too muddy to walk through. The group had to ask the locals who were with us on the boat about the height of the water on the left bank, and then the group estimated the horizontal extent visually.
6. The roughness coefficient chosen might actually be inaccurate, since it is only an estimate done through visual inspection.

Though it was only an approximate value, the group believes that the value for discharge at the time of the flooding obtained by slope-area method is fairly accurate.

7.2.0 MEASURING DISCHARGE WITH ACOUSTIC DOPPLER CURRENT PROFILERS (ADCP) FROM A MOVING BOAT

The ADCP uses the Doppler Effect to determine water velocity by sending a sound pulse into the water and measuring the change in frequency of that sound pulse reflected back to the ADCP by sediment or other particulates being transported in the water. The Doppler Effect is the phenomenon we experience when passed by a car or train that is sounding its horn. As the car or train passes, the sound of the horn seems to drop in frequency. The change in frequency, or Doppler Shift, that is measured by the ADCP is translated into water velocity. The sound is transmitted into the water from a transducer to the bottom of the river and receives return signals throughout the entire depth. The ADCP also uses acoustics to measure water depth by measuring the travel time of a pulse of sound to reach the river bottom and back to the ADCP.



7.2.1 SET-UP AND CALIBRATION

Before starting any process, the equipment was carefully assembled by mounting the sensors and transmitter on a meter long, yellow-colored plastic vessel. After synchronizing with a laptop computer, the ADCP was calibrated on its pitch, roll and yaw axes by actually yanking the assembled equipment to various orientations for at least a minute. After the calibration, the ADCP was positioned towards the left bank downstream of the bridge, coinciding with the first cross section of the previous-day slope-area measurements of the group.


7.2.2 TECHNIQUES AND RESULTS

Before the actual discharge measurements were taken, the distance from the transducer to the water edge on the left bank was first measured by a measuring tape and the information relayed to the team on the bridge in charge with the user interface of the ADCP. After the gauge height (4.65 meters) and the distance to water edge were entered on the user interface, the team using the computer signals the team on the boat to start moving across the river, towing the ADCP from left bank to right bank. Upon arriving at the opposite bank, the distance from the transducer to the water edge on the right bank was also taken and relayed to the team handling the computer. The same distance on the other bank was also measured. This process was done twice and vice versa. At that point, measurement was done and after a brief moment, results were displayed on the computer. Note that no tagline was used. The gauge height at the start and end of the method was recorded.


The ADCP actually measures the following values:

- a. Location of sampling verticals 1, 2, 3,...n across the stream in reference to the distance from an initial point;
- b. Stream depth, d , at each observation vertical;
- c. Stream velocity, V , perpendicular to the cross section at each observation vertical.

The results were shown graphically on the user interface. Data gathered could also be exported to a text file, for storage or documentation.



The group made four transects along the cross section, three of which have regions of invalid ensembles resulting from invalid bottom tracking. The last transect (shown above) has no invalid ensembles and was more accurate than the first three. Discharge measured at this transect was 441.287 cubic meters per second, at gauge height equal to 4.65 m.



7.2.3 CONCLUSION

By far, ADCP is the most convenient means of measuring discharge. Nonetheless, it has certain drawbacks:

1. High frequency pulses (“pings”) yield more precise data, but low frequency pulses

Highlighted portions show vertical bars below the stream bed, representing invalid ensembles resulting from invalid bottom tracking. Image taken from the first transect.

travel farther in the water. The discharge measurement team must make a compromise between the distance that the profiler can measure and the precision of the measurements. This is clearly illustrated by the black area above the stream bed in the ADCP output picture. Although velocities were accurately measured in most areas, the black areas show no velocity readings just above the stream bed. The obvious solution to this is to make the frequency of the pings lower so as to maximize the depth covered by the beam, but that would also affect the precision of the measurements.

2. Setting the ADCP at higher frequencies would deplete the batteries quickly.
3. Just the same as with measurements by current meter while on a boat, a tagline would greatly help in the accuracy of the data by ensuring that the measurements follow a straight line towards the other bank. In the group’s measurement, no tagline was used.
4. For the river surveyor model that was used, mishaps can happen in securing the transducer to the floater assembly. Even when fastened properly, there is still a possibility that the transducer will fall-off because it was merely inserted and fastened in place by a locking mechanism that does not entirely secure the whole instrument from falling off while in transit. This may be a limitation in the design of the model that was used.
5. It is expensive.

As can be seen on the output of the ADCP, water velocities at the edges are lower compared to the water velocities in the water column right above the thalweg. The output gives an illustration of the distribution of velocities within the cross section.

Measurements are all done via a computer, so the human elements of error in the calculations are eliminated. Care must be taken in the assembly, set-up, and actual traverse of the boat so as to yield optimum results. When all these are taken into consideration, ADCP measurements could serve as a benchmark for other traditional discharge measurements methods. It also gives the most accurate results.

7.3.0 DISCHARGE MEASUREMENT USING CURRENTMETER

In this method, the stream channel cross section is divided into numerous vertical subsections. In each subsection, the area is obtained by measuring the width and depth of the subsection, and the water velocity is determined using a current meter. The discharge in each subsection is computed by multiplying the subsection area by the measured velocity. The total discharge is then computed by summing the discharge of each subsection. The total discharge for the cross section would then be the sum of all the partial discharges. This is the basic idea of the current meter method




7.3.1 IDENTIFYING THE SEGMENTS

Measurements were done on the cross section directly below the bridge facing downstream. At the bridge, points were established starting from the left bank where the water edge was directly under. The group established several points where the measurements were to be taken based on the width of the river. The cross section was sub-divided into 24 segments having a 5 meter interval from the banks while switching to a 3 meter interval as the group approached middle portions of the river, in anticipation of greater depths. This was done so that the partial discharges may not exceed 10 percent of the total.

Depths at each point were then measured using an echo sounder prior to the actual measurement of velocities. This was done in order to know beforehand the depths at which we are required to measure velocity by 2-point method, considering the sounding reel's cable length. Apparently, the sounding reel available could not reach the bottom of the river as relayed by the previous groups who had done the current meter method.

7.3.2 VELOCITY MEASUREMENTS



After the locations of the verticals have been established, the price current meter was checked for proper calibration. The bucket wheel was spun and the duration of the spinning noted. For a well-calibrated price AA current meter, the spinning should last to 2 minutes. The current meter available, on the other hand, was only spinning for less than a minute. This would indicate that the price current meter was already due for calibration and maintenance.

The sounding reel was then set-up. Current meter parts were assembled by coupling the meter and the columbus weight thru a hanger bar and attached to the cable from the sounding reel. The depth indicator for the sounding reel and the current meter beeper (which counts every revolution of the rotor made) were then connected to the whole assembly. *The price current meter was set to give a beep for every 5 revolutions.*

The current meter assembly was positioned at the points earlier identified. The current meter was lowered so that it aligns with the bridge road, after which the depth indicator was set to zero. After setting to zero, the meter was again lowered down until it reached the water surface and the corresponding depth recorded as the height of the bridge to the water surface.

After lowering the current meter up to the water surface, the depth indicator is once again set to zero and afterwards the current meter was lowered to 20% and 80% of the depth at that vertical, guided by the procedures of the two-point method of current meter measurements (These depths were already predetermined by the depth measurements done with an echo sounder prior to the velocity measurements. See section 3.3.1). The angle formed by the cable from the normal was also measured, as these would have to be taken into consideration in discharge calculations. The count of the current meter beeper within a 60-70 second interval was then recorded at those depths within the vertical.


Velocity measurements are done at all the verticals identified until the whole cross section under the bridge was covered.

7.3.3 DISCHARGE CALCULATIONS

All the data gathered were entered in the excel suite for current meter discharge calculations provided by our instructor, Mr Hilton T. Hernando. The program used the mid-section method for discharge calculations and the group used the two-point method of velocity measurement (taking velocity measurements at 0.2 and 0.8 depths). Velocity formula for the current meter used was $V=0.702N+0.013$. Since the current meter was set to 1 beep per 5 revolutions, all the values for revolutions were multiplied by 5 prior to data entry. The summary of all data and calculations are shown below.

Discharge Measurement (Current Meter) for :				ARAYAT STATION				River:		PAMPANGA RIVER				PRFFC																	
DM #:		03		Date:		October 21, 2013				Team:		Group 3				FFB															
Gage Height:		Start:		3.16		End:		3.11		Inst. # :		1		Wx:		Fair		PAGASA													
Observation Time:		Start:		11:15		End:		14:42		Calibration Eqtn.: V =		0.702		N+		0.013		note: just input negative value													
		Vertical dist. to water surface (m) =				12.32								for latter if eqtn. is minus.																	
Total Area (m²) =				394.47				Ave. Gage Height =				3.14		Sectional Width (m) =		117.5															
Total Q (m³/s) =				293.42				Ave. Vel. (m/s) =				0.744																			
Dist. from				Depth		Vert.		Angle		Observation Depth				Velocity						Remarks											
Initial		Width		(ep for pier)		Angle		Corrected		0.2		0.6		0.8		at point		Mean		Area		Q		Excellent, Good							
point		(mts.)		(mts.)		4°-36°		Depth		Rev.		Time		Rev.		Time		Rev.		Time		for 0.6 only		(0.2 & 0.8)		(m²)		(cumecs)		Fair, Poor	
0								0																							
5		5		2.2		14.5		1.777		60		62.0						60		65		x		0.677		8.89		6.01			
10		5		3.6		23		2.464		90		60.7						60		63.94		x		0.863		12.32		10.63			
15		4		6		26		4.451		50		61.5						25		61.33		x		0.442		17.81		7.86			
18		3		7.7		21.5		6.602		90		62.2						80		60.62		x		0.984		19.81		19.50			
21		3.5		7.6		21		6.549		85		62.1						85		64.44		x		0.957		22.92		21.93			
25		2.85																												PIER	
26.7		4																												PIER	
33		4.65		8.4		24		7.020		80		60.82						45		65.35		x		0.716		32.64		23.38			
36		3		8.7		22		7.522		80		61.92						60		61.62		x		0.808		22.57		18.24			
39		3		9.3		13.5		8.874		85		63.71						60		62.39		x		0.819		26.62		21.80			
42		3		8.8		9.5		8.593		80		64.51						65		61.63		x		0.818		25.78		21.10			
45		3		8.1		6.5		8.007		80		63.45						50		65.27		x		0.724		24.02		17.40			
48		3		6.6		8.5		6.442		75		64.55						70		64.52		x		0.802		19.33		15.49			
51		3		6		12.5		5.660		75		61.17						60		65.6		x		0.764		16.98		12.98			
54		3		5.3				5.300		75		64.23						60		63.98		x		0.752		15.90		11.96			
57		3		4.6				4.600		80		63.35						60		64.26		x		0.784		13.80		10.82			
60		4		3.5				3.500		80		63.55						60		62.32		x		0.793		14.00		11.10			
65		5		3.6				3.600		75		61.99						55		61.06		x		0.754		18.00		13.57			
70		5		3.3				3.300		75		62.48						50		63.29		x		0.712		16.50		11.74			
75		5		2.7				2.700		75		64.57						55		63.57		x		0.724		13.50		9.78			
80		5		2.5		4		2.468		75		65.2						55		64.65		x		0.715		12.34		8.83			
85		7.4		2.4				2.400		70		61.5						55		65		x		0.710		17.76		12.60			
94.8		5.75																												PIER	
96.5		2.6																												PIER	
100		4.25		2.7				2.700		50		61.87						30		63.84		x		0.462		11.48		5.30			
105		5		1.2				1.200		25		62.54						20		88.39		x		0.233		6.00		1.40			
110		5		0.9				0.900						0		0						x		x		4.50		x			
115		3.75		0.27				0.270						0		0						x		x		1.01		x			
117.5		x		0				0.000						0		0						x		x		x		x			
251 Page												Total Area =				394.47															
Rem:												Total Discharge =				293.42															
												Ave. Velocity =				0.744															

Computation of Mean Gage Height by Q weighting Process						
Station :	ARAYAT STATION			Date :	October 21, 2013	
River :	PAMPANGA RIVER					
DM # :	03			M.G.H.	3.12	meters
Time (0000)	Gage Height Reading	Ave. Gage Height		Q _{total} ending at Time	Ave. G.H. * Q	Remarks
1115	3.15					
1200	3.12	3.135		65.93	206.69	
1300	3.12	3.120		101.93	318.01	
1400	3.11	3.115		97.44	303.52	
1442	3.08	3.095		28.12	87.04	
		x			x	
		x			x	
		x			x	
		x			x	
		x			x	
		x			x	
		x			x	
		x			x	
		x			x	
		x			x	
		x			x	
			Totals =	293.42	915.26	
			Mean Gage Height =	3.12	meters	



The group also noted that starting at 110 meters from the origin towards the water edge of the right bank, the current meter no longer registers a beep. Consequently, velocities at those points were recorded as 0. The discharge at the cross section under the bridge on the downstream side, as measured by current meter method at an average gage height of 3.14, was 293.42 cubic meters per second.

7.3.4 CONCLUSIONS

Discharge measurement using currentmeter can be used in low to high flows, but that depends on the situation. It is classified as a direct method of discharge measurement.

Like any other methods, current meter method also has its drawbacks:

1. The Price AA current meter used in the activity was a vertical axis current meter. This type of meter is prone to obstruction by rubbish that would stick either on its bucket wheel or on the shaft where it rotates. This could hinder the rotation and consequently give inaccurate results.
2. As mentioned earlier, the current meter may no longer register beeps at very low velocities. This also affects the accuracy of the calculations because at very low flows, velocity is taken as 0.
3. It is only optimal at depths greater than 2.5 feet (0.762 meters).
4. As with any other device, poor condition or calibration of the current meter may lead to error in the measurements. In fact, the price meter used in the activity was due for maintenance and/or recalibration; it failed the spin test.
5. When measuring atop a bridge, major errors are caused by the effects of the pier on the water current. Due to turbulence, velocities near the structure were no longer measured.

Discharge measurement using currentmeter may the most versatile method, it can be accurately calibrated, relatively quick and simple, its depth and width measurement are relatively easy. However, it has some disadvantages that cannot be neglected such as the meter is subject to damage, the calculation and taking changing flows take time, high velocities cause errors, and it can put people in dangerous situation.

Generally, the discharge made by the group would have been optimum if the current meter passed the spin test. But the computed discharge was, at best, already a good approximate.

7.4.0 DISCHARGE MEASUREMENT USING FLOATS

In this method, the velocity of the float is equal to the distance between the cross sections divided by the time of travel. The mean velocity of flow in the vertical is equal to the float velocity multiplied by a coefficient that is based on the shape of the vertical-velocity profile and relative depth of immersion of the float. Floats have limited use in stream gaging, and always best to be used during and after flood occurrence.


7.4.1 TECHNIQUES AND MEASUREMENTS

In float method of discharge measurement, bamboo floats were prepared. Flags were attached to one end of each bamboo. Sand was placed inside so that the bamboo would float vertically in the river. Two points along the river were measured and identified as the starting point and the end points. Floats are thrown into the river and the time it takes to reach a specified distance downstream from a starting point is measured. Since a predetermined distance is known, velocity can be measured from the travelling time. This method actually measures surface velocity; mean velocity is then estimated by multiplying surface velocity by a correction factor.

Much like the slope-area method, this indirect method of computing streamflow is generally applied for floods where discharge observation by current meter and ADCP is difficult. Measurement of water depth during floods is difficult, so only water surface elevation is recorded (or gauge height, depending on the datum used) and a cross section survey must be conducted soon after the flood to estimate the discharge area. Since float method requires velocity in the calculations, it has a higher accuracy compared to slope area method.



7.4.2 MEASUREMENT OF TRANSIT TIME



The group used the 1st and 2nd cross sections in their slope area measurements as boundaries of the actual measurement section; the approach section was about 53 meters (from the bridge to the 1st cross section) and measurement section at 150 meters (1st to the 2nd cross section). The group was divided into two teams; the 1st team drops the bamboo floater off the bridge and the 2nd team acts as spotters on the 1st and 2nd cross sections. There must be communication at all times during the activity since at all three points (bridge, start point, end point), the time measured must ideally be in sync.

The team on the bridge divided the river width into five (5) unequal intervals, taking into consideration the contracting feature of the river. It was inside these intervals that the bamboo floaters were dropped. The team on the bridge notifies everyone that the float was dropped in a given section, the spotter on the 1st cross section notifies everyone to start timing, and lastly, the spotter on the 2nd cross section signals everyone to stop the time. Individual records for the start as well as the end time were averaged, and the time elapsed computed for a given section.

There were a total of five (5) drop points and measurements were first done from the right bank towards the left bank and the gage height for the whole duration of the first pass was at 2.78 meters, which meant that the water level during the first set of measurements was at

2.862 meters AMSL (0 gage height at 0.082m AMSL). The bamboo floater resurfaced at all drop points during the first pass.

The second set of measurements was done from the left bank towards the right bank. Unlike the first pass, however, the floater did not resurface on the 1st and 2nd drop while floater did not move at the 5th drop. It was during this time frame that the water level at the arayat station started to significantly reduce due to the closure of the nearby dam (cong dadong dam). Due to the circumstances, readings on the 2nd pass were disregarded during the computations.

7.4.3 DISCHARGE AREA ESTIMATES


After determining the surface velocities, the discharge area at the time of float measurements would have to be estimated. This would be based on a survey done on the first and second cross sections of the 150-meter measurement section, which coincidentally are the same first and second cross sections being surveyed by another group doing the slope-area discharge measurements. The group went with the slope-area team in surveying the river bed elevation of the 2nd cross section (by echo sounder and range finder), while the slope area team used the depths recorded by the current meter team (on boat) to survey the river bed elevation of the 1st cross section. The group afterwards utilized the data from the survey of the 1st and 2nd cross sections done by the slope area team in determining the discharge area at the time that the floaters were dropped.

The data from the survey of the 1st and 2nd cross sections were plotted out on the cross section excel suite provided by Mr Hilton T. Hernando. The two cross sections were closed with a water surface elevation of 2.862 meters, which was the water elevation at the first set of float measurements (see section 3.4.1). The corresponding depths at the five (5) intervals were then determined from the difference between the water surface elevation and the elevation of the river bed at a given vertical/interval. The verticals/intervals are assumed to be in the same horizontal plane in both cross sections e.g. the first interval/vertical of the 1st cross section is aligned to the first interval/vertical of the 2nd cross section. However, because the river is contracting, the distance from right water edge to the first vertical and the distance from left water edge to last


vertical would not be the same for the two cross sections. This means that the two cross sections would have different widths and intervals.

A given section area would then be computed by multiplying the distance between verticals (interval) with the average of the depths at those verticals. There are a total of 5 sections for each cross section. The profiles of the cross sections are detailed below.

FIRST CROSS SECTION				
Interval	Distance	Accumulated distance	Depth	Section Area
0	0	0	0	0
1	47.17	47.17	2.452	57.83042
2	23	70.17	6.752	105.846
3	18	88.17	10.172	152.316
4	22	110.17	7.182	190.894
5	18.68	128.85	0	67.07988



SECOND CROSS SECTION				
Interval	Distance	Accumulated distance	Depth	Section area
0	0	0	0	0.00
1	26.8	26.8	0.942	12.62
2	18	44.8	1.532	22.27
3	18	62.8	2.572	36.94
4	22	84.8	3.402	65.71
5	22	106.8	0	37.42



7.4.4 DISCHARGE CALCULATIONS

After the areas at the time of velocity measurements have been determined for each subsection and in every cross section, the discharge can then be calculated. The velocity of the floats would be equal to the distance traversed (150 meters) divided by the time elapsed. The correction coefficient used to determine the average velocity was 0.92. The summary of the computations is shown on the next page.

Result of Discharge Observation By Float

Measuring Line	Time of Drop	Travelling Time (sec)	Velocity of Float (m/s)	Correction Coefficient	Corrected Velocity (m/s)	Divided Area (sq. meters)			Divided Q (cu. meters per second)
						Section 1	Section 2	Ave Area	
1	11:00 AM	732.07	0.20	0.92	0.19	57.83042	12.6228	35.22661	6.64
2	11:15 AM	198.95	0.75	0.92	0.69	105.846	22.266	64.056	44.43
3	11:20 AM	215.625	0.70	0.92	0.64	152.316	36.936	94.626	60.56
4	11:25 AM	194.23	0.77	0.92	0.71	190.894	65.714	128.304	91.16
5	11:30 AM	190.63	0.79	0.92	0.72	67.07988	37.422	52.25094	37.83
Total Discharge									240.62

The computed discharge by float method, at 2.78 gage height, was 240.62 cubic meters per second.

7.4.5 OBSERVATIONS AND CONCERNS

At the first drop point at the right bank, the flow was almost stagnant; the float in the first section took the longest time to traverse the whole 150 meter measurement section. In fact, during the second pass/measurement, the float did not move at all. This may be due to lower depths directly below the first drop point, lower velocities in that section, or both.

The second set of measurements was not considered for discharge calculations anymore because only 2 out of the 5 floats that were dropped gave reliable results. The 1st drop from the right bank did not show up on the surface, the second did show up but was upturned by the tagline at the first cross section and sank, and finally, the float did not move at the last drop point for the second set of measurements. It was also during these set of measurements that the gage height reduced significantly because of the irrigation dam that diverted the flow from the main river.

From these, the group concluded that discharge measurements by float method would not give the best results at low flows.

There were also issues regarding the track that the float follows as it traverses from the approach section and across the measurement section. The float does not follow a straight path and tends to go toward the adjacent subsection. This was especially pronounced at the first drop in the first set of measurements (first drop at the right bank) where the float significantly changed its course, going toward the second subsection instead of following a straight path from drop point. It was hard to ascertain whether it did enter the second subsection, but for ease in discharge calculations, it was assumed that all the floats went downstream in a straight line and within the subsection where it belongs.

7.4.6 CONCLUSION

Discharge measurements done via float method are optimal at medium to high flows. Like the slope-area method, it is an indirect method of computing discharge which can be best applied during flood events or at relatively high flows. It follows a simple and inexpensive way of measuring velocities, though a cross section survey would have to be done to estimate the discharge area so as to complete the discharge calculations.

It is less effective during low flows, where the floats (especially those of the stick-type like the bamboo used in the activity) have a high chance of being stocked on the river bed upon dropping. If the reach experiences very turbulent flow between points of measurement, the float could drastically change course, affecting the discharge measurements.

8.0 CONCLUSION ON THE VARIOUS METHODS OF DISCHARGE MEASUREMENTS

There are obviously different methods for computing discharge, as described in the previous sections. Each has their own merits and drawbacks. It would depend on the discharge measurement team's discretion on what method to use that would best suit the scenario at the time of measurement.

For instance, at the time of flooding, the most reasonable method to use would be the float method. A current meter used in that scenario, if it can be used at all, would easily be

destroyed. It would also be too much of a risk to use expensive equipment such as the ADCP in those situations. Even the float method has its drawbacks at high flows; the float can easily be lost from all the debris carried by floodwaters and also due to high turbulence. In the situations that cannot be covered by float-method, slope-area measurements are the best alternative in estimating discharge during flood events; the only drawback would be the tedious nature of survey work.

In scenarios other than flood events, measurements by current meters and ADCP's are the best methods to use. The ADCP gives the most accurate results with proper set-up, although current meters are the best, less costly alternative.

There is a method available for almost all scenarios. The decision on what to use for a given situation would depend on the judgment of the discharge measurement team.

9.0 DEVELOPMENT OF A RATING CURVE, EQUATION AND TABLE

One of the goals of discharge measurement is to establish a rating curve defined by measured discharges at various water surface elevations. Based on actual discharge data, an equation can be formulated that would best describe the observations in such a way that if the equation would be plotted out in a graph, the curve that forms "best-fit" the distribution of the data. With a rating equation, a hydrologist can estimate discharges at various water levels, even those water elevations not present in the actual data. The discharge for every water level, based on the rating equation, is then presented in a rating table. This would then serve as a guide for the hydrologist.

In the following sections, a rating curve will be established. Values for discharge at various levels of elevation are computed through an excel suite provided by Mr Hilton Hernando, which is based on manning's equation.

9.1 CROSS SECTION SURVEY

The cross section directly under the bridge on the downstream side will be used in estimating the discharge at various levels. For that, the elevation profile of the ground below the bridge would be needed. With the use of a sounding rope, group 1 of the HTC class did the survey for the area, measuring distances from the bridge railing to the ground below.

PAMPANGA RIVER BED PROFILING

Arayat, Pampanga

Start Time: 1342 HH

End Time 1405 HH

Date: Oct. 23, 2013

Bridge Measurements:

Height of Railing to Curb:


0.75 m

Height of Curb to Ground Level:

0.16 m

Measurements are taken from Top of the Bridge Railing, Left To Right of the Banks.

Station Interval	Depth (m)	Accumulated Horizontal Length (m)	Remarks	Station Interval	Depth (m)	Accumulated Horizontal Length (m)	Remarks
0	0.91	0	top of dike	6.2	14.18	158.34	
3.8	7.6	3.8	Foot of dike	5	13.36	163.34	
4.54	7.8	8.34		5	12.22	168.34	
5	7.8	13.34		5	10.95	173.34	
5	7.97	18.34		2.5	10.41	175.84	
5	7.97	23.34		2.5	9.93	178.34	
5	7.89	28.34		5	9.91	183.34	
5	9.26	33.34		5	9.91	188.34	
5	10.4	38.34		5	8.87	193.34	
5	11.17	43.34		5	9.16	198.34	
6.2	14.55	49.54	Left Water Edge	5	9.33	203.34	
3.8	15.57	53.34		5	9.33	208.34	
5	16.86	58.34		5	9.33	213.34	
5	19.88	63.34		5	9.33	218.34	
5	21.63	68.34		5	9.33	223.34	
10	21.57	78.34	Edge of Pier	5	9.59	228.34	
5	21.94	83.34		5	9.56	233.34	
5	22.48	88.34		5	9.56	238.34	
5	20.7	93.34		10	9.46	248.34	
5	19.39	98.34		5	9.71	253.34	
5	18	103.34		5	9.63	258.34	
5	17.63	108.34		5	9.05	263.34	
5	16.99	113.34		5	7.9	268.34	
5	16.79	118.34		5	7.77	273.34	
5	16.39	123.34		5	7.4	278.34	Foot of dike
5	15.97	128.34		14	0.91	292.34	top of dike
5	16.02	133.34					
5	16.51	138.34					
5	16.84	143.34					
5	15.78	148.34					
3.8	14.83	152.14	Right Water Edge				

PAMPANGA RIVER CROSS SECTION
SAN AGUSTIN BRIDGE, ARAYAT PAMPANGA

The survey did by group 1 measured only the distance from bridge railing to ground; the discharge calculations require ground elevation. To convert the given depths to MSL elevations, the MSL elevation of the bridge curb measured by group 4 was taken into account. The bridge curb was at 15.562 meters AMSL, and adding the height of the railing from the curb (0.75 meters), the MSL height of the bridge railing was at 16.312 meters. The difference between this value and the corresponding depths give out the elevations of the ground below the bridge.

The resulting data are the entered on a cross section excel suite that computes for width, area, wetted perimeter and hydraulic radius for a given water surface elevation. Note that in this survey, the bridge was assumed to be straight with no piers obstructing the river.

9.2 DISCHARGE ESTIMATION

				Date:	Oct. 23, 2013			
station	distance	elevation	water sfc.	depth	mean depth	area	wetted perimeter	remarks
0.00		15.402	15.40	0.00				
3.80	3.80	8.712	15.40	6.69	3.35	12.71	7.69	
8.34	4.54	8.512	15.40	6.89	6.79	30.83	4.54	
13.34	5.00	8.512	15.40	6.89	6.89	34.45	5.00	
18.34	5.00	8.342	15.40	7.06	6.98	34.88	5.00	
23.34	5.00	8.342	15.40	7.06	7.06	35.30	5.00	
28.34	5.00	8.422	15.40	6.98	7.02	35.10	5.00	
33.34	5.00	7.052	15.40	8.35	7.67	38.33	5.18	
38.34	5.00	5.912	15.40	9.49	8.92	44.60	5.13	
43.34	5.00	5.142	15.40	10.26	9.88	49.38	5.06	
49.54	6.20	1.762	15.40	13.64	11.95	74.09	7.06	
53.34	3.80	0.742	15.40	14.66	14.15	53.77	3.93	
58.34	5.00	-0.548	15.40	15.95	15.31	76.53	5.16	
63.34	5.00	-3.568	15.40	18.97	17.46	87.30	5.84	
68.34	5.00	-5.318	15.40	20.72	19.85	99.23	5.30	
78.34	10.00	-5.258	15.40	20.66	20.69	206.90	10.00	
83.34	5.00	-5.628	15.40	21.03	20.85	104.23	5.01	
88.34	5.00	-6.168	15.40	21.57	21.30	106.50	5.03	Thalweg
93.34	5.00	-4.388	15.40	19.79	20.68	103.40	5.31	
98.34	5.00	-3.078	15.40	18.48	19.14	95.68	5.17	
103.34	5.00	-1.688	15.40	17.09	17.79	88.93	5.19	
108.34	5.00	-1.318	15.40	16.72	16.91	84.53	5.01	
113.34	5.00	-0.678	15.40	16.08	16.40	82.00	5.04	
118.34	5.00	-0.478	15.40	15.88	15.98	79.90	5.00	
123.34	5.00	-0.078	15.40	15.48	15.68	78.40	5.02	
128.34	5.00	0.342	15.40	15.06	15.27	76.35	5.02	
133.34	5.00	0.292	15.40	15.11	15.09	75.43	5.00	
138.34	5.00	-0.198	15.40	15.60	15.36	76.78	5.02	
143.34	5.00	-0.528	15.40	15.93	15.77	78.83	5.01	
148.34	5.00	0.532	15.40	14.87	15.40	77.00	5.11	
152.14	3.80	1.482	15.40	13.92	14.40	54.70	3.92	
158.34	6.20	2.132	15.40	13.27	13.60	84.29	6.23	
163.34	5.00	2.952	15.40	12.45	12.86	64.30	5.07	
168.34	5.00	4.092	15.40	11.31	11.88	59.40	5.13	
173.34	5.00	5.362	15.40	10.04	10.68	53.38	5.16	
175.84	2.50	5.902	15.40	9.50	9.77	24.43	2.56	
178.34	2.50	6.382	15.40	9.02	9.26	23.15	2.55	
183.34	5.00	6.402	15.40	9.00	9.01	45.05	5.00	
188.34	5.00	6.402	15.40	9.00	9.00	45.00	5.00	
193.34	5.00	7.442	15.40	7.96	8.48	42.40	5.11	
198.34	5.00	7.152	15.40	8.25	8.11	40.53	5.01	
203.34	5.00	6.982	15.40	8.42	8.34	41.68	5.00	
208.34	5.00	6.982	15.40	8.42	8.42	42.10	5.00	
213.34	5.00	6.982	15.40	8.42	8.42	42.10	5.00	
218.34	5.00	6.982	15.40	8.42	8.42	42.10	5.00	
223.34	5.00	6.982	15.40	8.42	8.42	42.10	5.00	
228.34	5.00	6.722	15.40	8.68	8.55	42.75	5.01	
233.34	5.00	6.752	15.40	8.65	8.67	43.33	5.00	
238.34	5.00	6.752	15.40	8.65	8.65	43.25	5.00	
248.34	10.00	6.852	15.40	8.55	8.60	86.00	10.00	
253.34	5.00	6.602	15.40	8.80	8.68	43.38	5.01	
258.34	5.00	6.682	15.40	8.72	8.76	43.80	5.00	
263.34	5.00	7.262	15.40	8.14	8.43	42.15	5.03	
268.34	5.00	8.412	15.40	6.99	7.57	37.83	5.13	
273.34	5.00	8.542	15.40	6.86	6.93	34.63	5.00	
278.34	5.00	8.912	15.40	6.49	6.68	33.38	5.01	
292.34	14.00	15.402	15.40	0.00	3.25	45.43	15.43	
Total Width	292.34							
Total Area	3363.893							
W. P (P)	302.21							
Hydraulic Radius @	11.13098							
Mean sect. Depth	11.50678							

The table on the previous page shows the summary of the elevation profile of the whole cross section, enclosed with a water surface elevation equivalent to the elevation of the bridge railing in order to compute for the width, total area, wetted perimeter, and hydraulic radius when the water reaches the bridge railing. Computations for the mentioned parameters are repeated at other water surface elevations using the cross section sheet. There will be various values of these parameters for a whole range of water elevation, which are then entered in another excel suite that estimates discharge. The group's calculations are summarized below.

Pampanga River @ Arayat							
(based on cross-section undertaken on October 2013)							
Elevation of "0" of S.G.=	0.000	m.(AMSL)					
n=	0.030	I=	0.000145				
Elevation	Equivalent	Area	Width	W.P.	hyd radius	Discharge	Remarks
MSL (m)	G.H.(m)	a (m ²)	w (m)	s	r	Q (cumecs)	
15.40	15.402	3363.89	292.34	302.21	11.13	6731.22	bank full/ level with bridge road
15.00	15.000	3247.38	291.50	300.97	10.79	6364.56	
14.00	14.000	2956.91	288.60	297.38	9.94	5488.03	
13.00	13.000	2670.61	286.30	294.09	9.08	4665.80	
12.00	12.000	2385.26	283.15	290.25	8.22	3898.89	
11.00	11.000	2104.14	281.00	287.13	7.33	3186.39	
10.00	10.000	1824.65	278.00	283.48	6.44	2534.26	
9.00	9.000	1548.21	275.30	279.97	5.53	1943.30	
8.00	8.000	1291.18	236.10	240.54	5.37	1588.87	
7.00	7.000	1053.37	162.40	166.46	6.33	1446.52	
6.00	6.000	902.84	137.90	141.81	6.37	1244.84	
5.00	5.000	769.53	128.20	131.89	5.83	1001.07	
4.00	4.000	643.90	122.10	125.45	5.13	769.04	
3.00	3.000	525.10	116.30	119.21	4.40	566.34	
2.00	2.000	412.62	108.00	110.58	3.73	398.45	
1.00	1.000	310.25	98.00	100.34	3.09	264.30	
0.50	0.500	262.09	93.50	95.73	2.74	205.88	
-1.00	-1.000	163.04	56.40	57.80	2.82	130.64	
-2.00	-2.000	110.61	40.90	42.35	2.61	84.20	
-3.00	-3.000	72.23	36.90	37.84	1.91	44.61	
-4.00	-4.000	39.10	30.70	31.30	1.25	18.20	
-5.00	-5.000	11.85	25.00	25.27	0.47	2.87	1.168m from thalweg (thalweg @ 6.168 below MSL)

9.3 THE RATING EQUATION

From the previous calculations, a set of stage and discharge are now available for the whole range of the cross section. This time, the H-Q values are entered on another excel suite that computes for the rating equation. Shown on the next page are the H-Q values used for the rating equation computations.

Rating Curve Development for				Pampanga River		
Measuring Station:				Arayat Station		
Drainage Area:				6487		
River:				Pampanga River		
Location:				San Agustin Bridge, Arayat, Pampanga		
Elev. S.G. "0" rdg.=				0.000	meters	
Meas. #	Day	Month	Year	S.G.(m)	Q(m ³ /sec)	Remarks
				15.402	6731.219	
				14.000	5488.026	
				13.000	4665.799	
				11.000	3186.386	
				10.000	2534.263	
				9.000	1943.296	
				8.000	1588.867	
				7.000	1446.523	
				6.000	1244.836	
				5.000	1001.068	
				4.000	769.036	
				3.000	566.342	
				2.000	398.449	
				1.000	264.299	
				0.500	205.881	
				-1.000	130.644	
				-2.000	84.195	
				-3.000	44.612	
				-4.000	18.203	
				-5.000	2.871	

After the H-Q Values are entered, the value for Ho (elevation of zero flow) would have to be determined by trial and error on the “rat” tab of the same excel suite:

Summary test for Ho						
Ho	a	b	ΣX^2			
-7.50	0.26	3.239	159.0038	Minimum	$\Sigma X^2 =$	157.77577
-7.39	0.31	3.190	157.7758			
-7.28	0.36	3.140	160.9545			
-7.17	0.42	3.090	169.2081			
-7.06	0.49	3.039	183.3305			
-6.95	0.58	2.986	204.2726			
-6.84	0.68	2.933	233.1833			
-6.73	0.81	2.879	271.4649			
-6.62	0.96	2.824	320.8478			
-6.51	1.14	2.767	383.4949			
-6.40	1.35	2.708	462.1486			
-6.29	1.62	2.648	560.3451			
-6.18	1.94	2.586	682.7326			
-6.07	2.34	2.521	835.5621			

Assumed Ho =		-7.39	meters					
S.G. elev. (H)	H-Ho	Log H-Ho (X)	Log Q (Y)	X ²	XY			
15.402	22.792	1.358	3.828	1.844	5.198			
14.000	21.390	1.330	3.739	1.769	4.974			
13.000	20.390	1.309	3.669	1.715	4.804	n =		20.000
11.000	18.390	1.265	3.503	1.599	4.430	$\Sigma(X) =$		20.237
10.000	17.390	1.240	3.404	1.538	4.222	$\Sigma(Y) =$		54.273
9.000	16.390	1.215	3.289	1.475	3.994	$\Sigma(X^2) =$		21.930
8.000	15.390	1.187	3.201	1.410	3.800	$\Sigma(XY) =$		59.554
7.000	14.390	1.158	3.160	1.341	3.660			
6.000	13.390	1.127	3.095	1.270	3.488	$X_{\text{bar}} =$		1.012
5.000	12.390	1.093	3.000	1.195	3.280	$Y_{\text{bar}} =$		2.714
4.000	11.390	1.057	2.886	1.116	3.049	$(\Sigma(X))^2 =$		409.529
3.000	10.390	1.017	2.753	1.034	2.799			
2.000	9.390	0.973	2.600	0.946	2.529	$b^{\wedge} =$		3.190
1.000	8.390	0.924	2.422	0.853	2.237	$a^{\wedge} =$		-0.514
0.500	7.890	0.897	2.314	0.805	2.075	$a = 10^{a^{\wedge}} =$		0.306
-1.000	6.390	0.806	2.116	0.649	1.705	$b = b^{\wedge} =$		3.190
-2.000	5.390	0.732	1.925	0.535	1.409			
-3.000	4.390	0.642	1.649	0.413	1.060			
-4.000	3.390	0.530	1.260	0.281	0.668			
-5.000	2.390	0.378	0.458	0.143	0.173			

Meas. #	Day	Month	Year	S.G.(m)	Q(m ³ /sec)	Remarks
				15.402	6731.219	
				14.000	5488.026	
				13.000	4665.799	
				11.000	3186.386	
				10.000	2534.263	
				9.000	1943.296	
				8.000	1588.867	
				7.000	1446.523	
				6.000	1244.836	
				5.000	1001.068	
				4.000	769.036	
				3.000	566.342	
				2.000	398.449	
				1.000	264.299	
				0.500	205.881	
				-1.000	130.644	
				-2.000	84.195	
				-3.000	44.612	
				-4.000	18.203	
				-5.000	2.871	
				Q = 0.306	[H - (-7.39)]	3.190

38 | Page

The Rating Curve Equation !!!

The rating curve equation, from the given set of stage-discharge values, is:

$$Q = 0.306 (H+7.39)^{3.190}$$

9.4 THE RATING TABLE

After the rating curve equation has been computed, a rating table can be made. This is done on another excel suite that specifically creates a table based on the equation. The constants of the equation and gage height range are entered in the excel file, after which, it automatically gives the table:

Rating Table for:		Arayat				Date:		October 23, 2013		
River:	Pampanga			Location:		San Agustin, Arayat, Pampanga				
Elevation of S.G. "0" reading:		0								
Rating Curve Equation Coefficients: a =		0.306		Ho=		-7.390		b^=		3.190
Range of G.H.:		Min. G.H. =		0		Max. possible G.H.=		11.00		
Remarks:	readings based on MSL									
G.H.(m)	0.00	0.01	0.02	0.03	0.04	0.05	0.06	0.07	0.08	0.09
0.0	180.59	181.37	182.16	182.94	183.73	184.52	185.31	186.11	186.90	187.70
0.1	188.50	189.31	190.11	190.92	191.73	192.55	193.36	194.18	195.00	195.82
0.2	196.65	197.48	198.31	199.14	199.97	200.81	201.65	202.49	203.34	204.18
0.3	205.03	205.89	206.74	207.60	208.46	209.32	210.18	211.05	211.92	212.79
0.4	213.66	214.54	215.42	216.30	217.18	218.07	218.96	219.85	220.74	221.64
0.5	222.53	223.44	224.34	225.24	226.15	227.06	227.98	228.89	229.81	230.73
0.6	231.66	232.58	233.51	234.44	235.38	236.31	237.25	238.19	239.14	240.08
0.7	241.03	241.99	242.94	243.90	244.86	245.82	246.78	247.75	248.72	249.69
0.8	250.67	251.64	252.62	253.61	254.59	255.58	256.57	257.57	258.56	259.56
0.9	260.56	261.57	262.57	263.58	264.59	265.61	266.63	267.65	268.67	269.69
1.0	270.72	271.75	272.79	273.82	274.86	275.90	276.95	277.99	279.04	280.09
1.1	281.15	282.21	283.27	284.33	285.40	286.47	287.54	288.61	289.69	290.77
1.2	291.85	292.94	294.02	295.11	296.21	297.30	298.40	299.50	300.61	301.72
1.3	302.83	303.94	305.06	306.17	307.30	308.42	309.55	310.68	311.81	312.95
1.4	314.08	315.23	316.37	317.52	318.67	319.82	320.97	322.13	323.29	324.46
1.5	325.63	326.80	327.97	329.14	330.32	331.50	332.69	333.88	335.07	336.26
1.6	337.45	338.65	339.85	341.06	342.27	343.48	344.69	345.91	347.13	348.35
1.7	349.57	350.80	352.03	353.27	354.51	355.75	356.99	358.23	359.48	360.74
1.8	361.99	363.25	364.51	365.77	367.04	368.31	369.58	370.86	372.14	373.42
1.9	374.71	375.99	377.29	378.58	379.88	381.18	382.48	383.79	385.10	386.41
2.0	387.73	389.04	390.37	391.69	393.02	394.35	395.68	397.02	398.36	399.71
2.1	401.05	402.40	403.75	405.11	406.47	407.83	409.20	410.57	411.94	413.31

9.5 OTHER CONSIDERATIONS

The values in the rating table follow closely to the H-Q values that were supplied. Upon further inspection, it can be seen that the values for discharge for a given level varies greatly when compared to actual discharge measurements outlined in the previous sections. This may be due to the many assumptions considered at the start:

1. The H-Q values used in the formulation of the rating equation are in themselves only estimates computed based on manning's equation. The error may have been magnified when the rating curve equation and the rating table are computed.
2. The bridge was assumed to be straight. In reality, the bridge's elevation varies in certain sections.
3. The bridge was assumed to have no piers when it fact, it does. Piers affect water velocity surrounding its perimeter, and consequently, also affect discharge to a certain degree. Only the elevation of the river bed without the pier was considered.
4. The roughness coefficient used may have been inaccurate.
5. There might have been an error in evaluating the H_o . Since this was done by trial and error, other values for H_o that were not tried might have given closer results.

This section illustrates how rating curve equations are formulated and how rating tables are computed. If the values entered in the rating curve equation excel suite were actual discharge measurements on field, the resulting table will yield more accurate and reliable results.

10.0 FIELD VISITS

The fieldtrip/ fieldwork activities were made for ten days, and since the actual fieldwork was only good for four days, most of the time was spent on field visits. These areas being visited had a huge relation to the field of hydrology. It was somehow very relevant to the Hydrologists Training Course.

10.1 LA MESA DAM (October 15, 2013)



The La Mesa Dam ($14^{\circ}43'29''\text{N}$, $121^{\circ}5'11''\text{E}$) in Quezon is part of the Angat-Ipo-La Mesa water system, which supplies most of the water supply of Metro Manila. The La Mesa Dam is an earth dam whose reservoir can hold up to 50.5 million cubic meters occupying an area of 27 square kilometers. The water collected in the reservoir is treated on-site by the Maynilad Water Services, and at the Balara Treatment Plant further south by the Manila Water.

The visit in La Mesa Dam put an end to some of my questions about how a dam is operated and supplies quality water to the community, as lectured by the staff of the dam. It was then that I discovered the importance of its operation and maintenance, being aware of its use for some areas in Metro Manila.

10.2 PANTABANGAN DAM (October 19, 2013)



Pantabangan Dam, an earth-fill embankment dam on the Pampanga River located in Pantabangan, Nueva Ecija, is a multi-purpose dam that provides water for irrigation and hydroelectric power generation while its reservoir, Pantabangan Lake, affords flood control. It is 351 feet tall and 5,299 feet long and designed to withstand intensity 10 earthquakes. It can irrigate a maximum of 102,000 hectares of agricultural lands, benefiting the farmers.

The visit in Pantabangan Dam has specified a lot of information and knowledge about its use, operation and maintenance. The dam provides livelihood for the town as it is a good source of fish products.

It is also best for recreational activities and one of the destinations for fieldtrips and educational tours. Pantabangan Dam has a flood forecasting station that always monitors the water level in the dam and in the upstream rivers. However, there were some instruments that weren't working. Unlike the La Mesa Dam, the Pantabangan Dam has 3 spillway gates. Whenever the forecast of the water level reaches the critical level, water must be released before the actual event happens to avoid casualties. The forecasting station is also the one who notifies the community regarding any flooding events that may happen.

10.3 CONG DADONG DAM (October 21, 2013)



Cong Dadong Dam ($15^{\circ}11'2''\text{N}$, $120^{\circ}46'32''\text{E}$), located upstream of the Pampanga River, diverts the waters from the Pampanga and Rio Chico Rivers to the canals leading to farms in Arayat, Sta ana, San Luis, Candaba, San Simon and Apalit Towns. When the huge gates of the dam are closed, water passes through the left side of dam then to the canals and causes the drop of water level of the streams below the dam. These waters are used for the irrigation system of Province. A fish ladder was also installed just after the gates as another source of living. Whenever the gates of the dam are closed, for irrigation purposes, the water level downstream of the dam lowers.

The visit in Cong Dadong Dam was indeed an actual educational tour in such a way that the entire area was explored by us and put us into a feeling of amusement. It was that day that we came to a realization that the dam worth 3.4 billion pesos, designed to irrigate 10,270 hectares of farms in seven eastern towns, and was named after President Diosdado Macapagal. The visit is somehow relevant to hydrology by just observing the environment of the dam area, and how it was estimated and built for a great purpose.

10.4 MDRRMC CALUMPIT, BULACAN (October 23, 2013)

The visit in Calumpit, Bulacan to explore its well-known Municipal Disaster Risk Reduction and Management Council was very significant. I can see the passion of the staffs and volunteers, and how they discipline and train themselves for a hazard response. They have their



own excellent way on the awareness, preparation and response for a calamity. Trained response team was sent to seminars and educational activities and they have an outstanding excel application for hazard assessment and dissemination. The MDRRMC of Calumpit, Bulacan is one of the best MDRRMC in the country.

10.5 ANGAT DAM (October 24, 2013)



Angat Dam ($14^{\circ}54'29''\text{N}$, $121^{\circ}9'36''\text{E}$), located in Barangay San Lorenzo, Norzagaray, Bulacan, is a concrete water reservoir embankment hydroelectric dam that supplies the Manila metropolitan area water. The reservoir supplies about 90 percent of raw water requirements for Metro Manila through the facilities of the Metropolitan Waterworks and Sewerage System and it irrigates about 28,000 hectares of farmland in the provinces of Bulacan and Pampanga. The height of the dam is 131 meters its length had 568 meters, and base width of 550 meters. The Angat reservoir had a Capacity of 850 million cubic meters of water.

The visit in Angat Dam clarifies my doubts on its operation and management. The dam does not only supply the water needs of Metro Manila and other Provinces but is also a hydroelectric generating plant it had 10 vertical shaft, using Francis type water turbine that Includes turbines from the main powerhouse and the auxiliary powerhouse that generates capacity of 256,000 kW of electricity. Just like other dams, the visit in Angat Dam was very relevant to the field of hydrology and very informative in one way or another.

10.6 BACOLOR CHURCH

Bacolor Church is one of the oldest and largest churches in the Philippines, located in the former Philippine capital (Bacolor). It was constructed by the Augustinian friars in 1576 on the lot of Don Guillermo Manabat, a rich landlord believed to be the founder of Bacolor. The church was restored by Fr. Manuel Diaz in 1897. It has a central nave and well-lighted transept with windows. The main retablo, side retablos and pulpit are gilded with gold leaf. The richness of the decoration of Bacolor church depicts advanced stage of baroque and rococo. In spite of the 1991 eruption of Mt. Pinatubo which half-buried the church on October 1, 1995, the structure is still being used as place of worship. It was already a world renowned tourist destination prior to the lahar tragedies; now more tourists flock to the church which remaining features are being preserved and maintained.

The visit in Bacolor Church is not somehow related to hydrology, but it was good of the HTC and PRFFWC staffs to remember and include God in this 10-day field activities.



11.0 FIELDTRIP/FIELDWORK EVALUATION

The entire fieldwork was very necessary to the training course and very useful and relevant in preparation and training to be the country's future hydrologists. The day to day scheduled activities may not be flawless, as all things are subjected to different mistakes, it was indeed one of the best and most exciting part of HTC that covers up the basic applications and information of the nature of works of the hydrologists. Therefore, I recommend fieldwork activities and fieldtrips for the training courses of PAGASA in the future.